







Description:

Grandway's Fiber Termination Box provides a high density wall mounted solution for next generation networks, which aims to provide and manage maximum numbers of fiber termination in a limited space. It is normally installed in the way of wall mounting or pole mounting.

Features:

- 1. Water-proof design with IP65 Protection level
- 2. Integrated with splice cassette and cable management system
- 3. Manage fibers in a reasonable fiber radius condition
- 4. Uncutting design
- 5. Fiber bend radius control more than 40mm
- 6. Suitable for the fusion splice or mechanical splice
- 7. 12 ports cable entrance for FTTH drop cable

Configuration:

Materia	Size	Max Capacity	Empty Weight	Loaded Weight	Color
---------	------	--------------	--------------	---------------	-------



2							
PC+ABS	A*B*C(mm)	SC	LC	1.2.kg	1.6kg	White	
	250*190*39	12 Ports	24 Ports				

How to order a Grandway Fiber Termination Box?

Model Rules: F2H-FTB-12-A-XX-XX

Model	Capacity	Туре	XX: Adapter	XX: Pigtail
FTB	12	A	SC: SC/UPC	SC: SC/UPC
			AS: SC/APC	AS: SC/APC
			LC: LC/UPC	LC: LC/UPC
			AL: LC/APC	AL: LC/APC